



| | |
|--------------------------|--------------------------------------|
| Housing Color / Material | Grey / Fiberglass Reinforced Plastic |
|--------------------------|--------------------------------------|

| | |
|----------------------------|------------|
| Type of Contact / Material | Screw / Sn |
|----------------------------|------------|

| | |
|-----------------|-------|
| Contact Spacing | 18 mm |
|-----------------|-------|

| | |
|---------------------|----------------------|
| Cable Entry / Range | PG 11 / 4.5 to 11 mm |
|---------------------|----------------------|

| | |
|-----------------------|-----------------|
| Max Voltage / Current | 250 V / 16 amps |
|-----------------------|-----------------|

| | |
|-----------------|------------------|
| Number of Poles | 3 Poles + Ground |
|-----------------|------------------|

| | |
|------------------------|--------|
| Maximum Conductor Size | 16 awg |
|------------------------|--------|

| | |
|--------------|------------|
| Fixing Screw | M3 x 35 mm |
|--------------|------------|

| | |
|--------|-------------|
| Gasket | NBR Profile |
|--------|-------------|

| | |
|-----------------------|-------------------|
| Operating Temperature | - 40 F to + 257 F |
|-----------------------|-------------------|

| | |
|------------------|-------|
| Protection Class | IP 65 |
|------------------|-------|

| | |
|-----------|-----------------------------|
| Approvals | UR, VDE, SEV, CSA, CE, ROHS |
|-----------|-----------------------------|

No Circuit

P/N: GDMZ RG 311 0 316 0



33801 Curtis Blvd #110
 Eastlake, Oh 44059
 Ph: 800-966-2345
 Fx: 440-942-2102
 Web: www.majordin43650.com