



Product information SPIDER III - Standard Line (SL) and Premium Line (PL) - SPIDER-SL-40-08T1999999SY9HHHH

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER III-Switches:SPIDER III - Standard Line (SL) and Premium Line (PL)

<http://dev-catalog.beldensolutions.com/link/57078-24455-49855-437329-506205/en/SPIDER-SL-40-08T1999999SY9HHHH/ui/state>

Name	SPIDER III - Standard Line (SL) and Premium Line (PL)
	
	Unmanaged, Industrial ETHERNET Rail Switch, fanless design, store and forward switching mode, Full Gigabit Ethernet
Delivery informations	
Availability	available
Product description	
Description	Unmanaged, Industrial ETHERNET Rail Switch, fanless design, store and forward switching mode, Full Gigabit Ethernet
Port type and quantity	8x 10/100/1000BASE-T, TP cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity
Type	SPIDER-SL-40-08T1999999SY9HHHH
Order No.	942 132-004
More Interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 3-pin,
Network size - length of cable	
Twisted pair (TP)	0 m ... 100 m
Network size - cascading	
Line - / star topology	any
Power requirements	
Operating voltage	12/24 V DC (9.6 - 32 V DC)
Current consumption at 24 V DC	Max. 200 mA
Power consumption	Max. 5.0 W, 17.1 Btu (IT) h
Ambient conditions	
Operating temperature	0 °C ... 60 °C
Storage/transport temperature	-40 °C ... 70 °C
Relative humidity (non-condensing)	0 % ... 95 %
MTBF (Telcordia)	1.207.249 hours; Telcordia SR-332; Gb 25°C
Mechanical construction	
Dimensions (W x H x D)	38 x 102 x 79 mm (w/o terminal block)
Mounting	DIN Rail
Weight	170 g
Protection class	IP30 (plastic housing)
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	3.5 mm, 5-8.4 Hz, 10 cycles, 1 octave/min; 1 g, 8.4-150 Hz, 10 cycles, 1 octave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80-1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz-80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Service	
Diagnostics	LEDs (power, link status, data, data rate)
Approvals	
Safety of industrial control equipment	cUL 61010-1/61010-2-201

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER III-Switches:SPIDER III - Standard Line (SL) and Premium Line (PL)

<http://dev-catalog.beldensolutions.com/link/57078-24455-49855-437329-506205/en/SPIDER-SL-40-08T1999999SY9HHHH/uistate>

Scope of delivery and accessories

Scope of delivery	Device, terminal block, safety instruction
Accessories	Rail Power Supply RPS 30/80 EEC/120 EEC (CC), Wall mounting plate for DIN rail mounting 40mm - order nr. 942 177-001,wall mounting plate for DIN rail mounting 70mm - order nr. 942 177-002

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.